

















Level of use EN 1470	class 33 heavy duty						
Emission tested acc. to DIBt principles acc. to CRI principles	abZ-Nr.: Z-156.601-401 Green Label Plus 2655						
Health safety Environmental label RAL-UZ 128	Blue Angel Contract No.: 19064						
Wear layer	100% polyamide dorix						
Back	PAN/PES-fleece with PP mesh						
Total thickness ISO 1765	6,5 mm						
Total weight ISO 8543	1500 g/m ²						
Fibre weight	750 g/m ²						
Dimensions	roll width 200 cm / roll length 25-35 lm						
Fire rating EN 13501-1	Bfl-s1						
Sound absorption ISO 10140	23 dB						
Level of sound absorption ISO 354	Freq. Hz	125	250	500	1000	2000	4000
	α _s	0,01	0,01	0,09	0,18	0,41	0,63
	α _w	0,20					
Colour fastness to light ISO 105-B02	6-7						
Thermal resistance ISO 8302	0,13 m ² K/W suitable for underfloor heating						
Anti-Static ISO 6356	≤ 0,5 kV						
Resistance to earth EN 61340-4-1 (glued conductively)	≤ 1 x 10 ⁹ Ω						
Special colours	> 1000 m ²						
Installation DIN 18365	For the correct installation of our textile floorings use only ultra low emission adhesives, free of low-, middle- and high boiling solvents and with very high shear strength (> 2 N/mm ² , in accordance with EN 14293). A list of suitable adhesives is available on request.						

Subject to improvements and usual colour deviations. The explanations in our technical instruction card as well as our cleaning and maintenance instructions have to be observed. Additional technical details upon request.

 heavy duty									 12 Hersteller: Findeisen GmbH Bulacher Str. 53 76275 Ettlingen EN 14041:2004  Bfl-s1  DS EN 1470
									

FINDEISEN GmbH

Bulacher Str. 53 | D-76275 Ettlingen | Telefon +49 7243 7100-0 | Telefax +49 7243 12760 | info@finett.de | www.findeisen-nadelvlies.de