

MIPOLAM ACCORD

gerflor.com

Mipolam Accord

TECHNICKÉ PARAMETRE

Celková hrúbka	EN ISO 24346 (EN 428)	mm	2,00
Hmotnosť	EN ISO 23997 (EN 430)	g/m ²	2780
Šírka/dĺžka pásu	EN ISO 24341 (EN 426)	cm/bm	200/20
Rozmer štvorca	EN ISO 24342 (EN 427)	mm	608 x 608 ⁽¹⁾
Počet štvorcov v balení	-	-	20

KLASIFIKÁCIA

Norma/Špecifikácia produktu	-	-	EN ISO 10581 (EN 649)
Európska klasifikácia	EN ISO 10874 (EN 685)	trieda	34-43
Horľavosť	EN 13501-1	trieda	B _{fl} - s1
Vznik el. náboja	EN 1815	kV	< 2
Protišmykovosť	DIN 51130	trieda	R9

VÝKONNOSTNÉ PARAMETRE

Odolnosť voči oderu	EN 660.2	mm ³	≤ 2.0
Skupina oderuvzdornosti	NF 189	skupina	T
Obsah spojiva	ISO 10581	typ	I
Rozmerová stálosť	EN ISO 23999 (EN 434)	%	Sheet ≤ 0.40 - Tile ≤ 0.25
Reziduálna trvalá deformácia	EN ISO 24343-1 (EN	mm	≈ 0.02
Test kolieskovej stoličky (type W)	ISO 4918 (EN 425)	-	OK
Tepelná vodivosť	EN ISO 10456	W/(m.K)	0,25
Stálofarebnosť	EN 20 105 - B02	stupeň	≥ 6
Povrchová úprava	-	-	Evercare™
Odolnosť voči chemikáliám	EN ISO 26987 (EN 423)	trieda	OK
Antibakteriálna a protiplesňová ochrana	ISO 22196	-	> 99 % brzdenie rastu

Životné prostredie

TVOC po 28 dňoch	ISO 16000-6	µg/m ³	< 10
Certifikácia	-	-	Floorscore™

CE marking

CE	EN 14041	-	
	-	-	

- (1) Products available in tiles for a minimum quantity order of 500 sq.m
 (2) The implementation of an effective cleaning method is the best defence against infection

Installation and Maintenance Guidelines, Complementary ranges available on our Gerflor website.

Product description and technical data sheet available in various languages. See our Gerflor Country websites.

Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

IMPORTANT: The information contained in this document is valid from 30/04/2017 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

MIPOLAM ACCORD, LESS SPEAKING FOR MORE ACTIONS

 COMPOSITION 100% REACH compliant	 INDOOR AIR QUALITY 100 times lower than norm requirements (TVOC < 10 µg/m ³ after 28 days)	 RECYCLED CONTENT 25%	 RECYCLABILITY 100%	 LCA Eco-designed according to a product specific life cycle analysis	 WELLNESS Walking comfort <75dB
--	--	------------------------------------	----------------------------------	--	--

Be **CONNECTED!**



Gerflor
 theflooringgroup