






DESCRIPTION			
Total thickness	EN ISO 24346 [EN 428]	mm	2.00
	ASTM F386-02	inch	0.08
Weight	EN ISO 23997 [EN 430]	g/sq.m	3300
Width of sheet	EN ISO 24341 [EN 426]	cm	200
	-	Feet-inch	6'6"
Lenght of sheet	EN ISO 24341 [EN 426]	lm	20
	-	Feet-inch	66'
Tile size	EN ISO 24342 (EN 427)	mm	608 x 608
Number of tiles per box	-	-	20
CLASSIFICATION			
Norm / Product Specification	-	-	EN ISO 10581 [EN 649]
	ASTM F 1913-04	-	compliant
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13 501-1	class	B _{fl} -s1
	ASTM E648-08	class	Class I
	CAN /ULCS102.2	-	tested in accordance
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet	DIN 51130	class	R9
PERFORMANCE			
Wear resistance	EN 660.2	mm ³	≤ 7.5
Wear group	NF 189	group	M
Type binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999 [EN 434]	%	sheet ≤ 0.40 tile ≤ 0.25
Impact sound insulation	EN ISO 717-2	dB	4
Residual indentation	EN ISO 24343-1 [EN 433]	mm	~ 0.03
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN12524)	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Chemical products resistance (1)	EN ISO 26987 [EN 423]	-	OK
Anti-bacterial activity (E. coli – S.aureus – MRSA) (2)	ISO 22196	-	> 99 % inhibits growth
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041	-	  
		-	

(1) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.

(2) The implementation of an effective cleaning method is the best defence against infection.